Central Steel & Wire Company

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 08/28/2018

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Stainless Steels

Synonyms: Bar, Sheet, Plate, Tubing, Pipe, Structurals

1.2. Intended Use of the Product

Solid Product, Various Forms and Uses.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Central Steel & Wire 3000 West 51st Street Chicago, IL 60632 Tel: 773-471-3800

1.4. Emergency Telephone Number

Emergency Number : CHEMTREC (US Transportation): (800) 424-9300 CANUTEC (Canadian Transportation): (613) 996-6666

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC - Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

 Skin Sens. 1
 H317

 Carc. 1B
 H350

 Repr. 1B
 H360

Full text of hazard classes and H-statements: see Section 16.

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)





Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

 $\mbox{H360}\mbox{ -}\mbox{May}$ damage fertility or the unborn child.

Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing fume, dust.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see Section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

08/28/2018 EN (English US) 1/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

2.3. Other Hazards

This product as shipped is physiologically inert in its solid form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish. The below listing is a summary of elements used in alloying stainless steels. Various grades will contain different combinations of these elements. Other trace elements may also be present in minute amounts. These small quantities (less than 0.1%), frequently referred to as "trace" or "residual" elements, generally originate in the raw material used. Values shown are applicable to component elements. *Stainless steel products as provided contain chromium metal in the zero valence state. As such, chromium metal does not present any unusual health hazard. However, welding, torch cutting, brazing, or perhaps grinding of chromium metal in stainless steel may generate airborne concentration of hexavalent chromium. The roll may have a light coating of oil to prevent corrosion.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Iron	(CAS-No.) 7439-89-6	45 - 90	Comb. Dust
Nickel	(CAS-No.) 7440-02-0	<= 46	Skin Sens. 1, H317
			Carc. 2, H351
			STOT RE 1, H372
			Comb. Dust
Chromium	(CAS-No.) 7440-47-3	10 - 30	Comb. Dust
Manganese	(CAS-No.) 7439-96-5	<= 15	Comb. Dust
Molybdenum	(CAS-No.) 7439-98-7	<= 7	Comb. Dust
Silicon	(CAS-No.) 7440-21-3	<= 6.5	Comb. Dust
Copper	(CAS-No.) 7440-50-8	<= 5	Comb. Dust
Cobalt	(CAS-No.) 7440-48-4	<= 5	Acute Tox. 4 (Oral), H302
			Acute Tox. 1 (Inhalation:dust,mist), H330
			Eye Irrit. 2A, H319
			Resp. Sens. 1B, H334
			Skin Sens. 1, H317
			Carc. 1B, H350
			Repr. 2, H361
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
			Comb. Dust
Tungsten	(CAS-No.) 7440-33-7	<= 4	Comb. Dust
Aluminum	(CAS-No.) 7429-90-5	<= 4	Comb. Dust
Titanium	(CAS-No.) 7440-32-6	<= 2.4	Comb. Dust
Carbon	(CAS-No.) 7440-44-0	<= 2	Comb. Dust
Vanadium	(CAS-No.) 7440-62-2	<= 1.1	Comb. Dust
Tantalum	(CAS-No.) 7440-25-7	<= 1	Comb. Dust
Niobium	(CAS-No.) 7440-03-1	<= 1	Not classified
Lead	(CAS-No.) 7439-92-1	< 0.1	Carc. 1B, H350
			Lact, H362
			Repr. 1A, H360
			STOT RE 1, H372
			Comb. Dust
Paraffin oils	(CAS-No.) 8012-95-1	< 0.1	Acute Tox. 4 (Inhalation:dust,mist), H332
			Asp. Tox. 1, H304
			Aquatic Chronic 4, H413
Nitrogen	(CAS-No.) 7727-37-9	<= 0.06	Simple Asphy
			Press. Gas (Comp.), H280

08/28/2018 EN (English US) 2/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Sulfur	(CAS-No.) 7704-34-9	<= 0.06	Skin Irrit. 2, H315
			Aquatic Acute 3, H402
			Comb. Dust

Full text of H-phrases: see Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: If injury occurs or if you feel unwell seek medical advice.

Inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Remove contaminated clothing. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization. May cause cancer. May damage fertility or the unborn child. Under normal conditions of use not expected to present a significant hazard. Under milling, or physical alteration metal dusts may be produced that cause irritation of the respiratory tract, skin, and may be harmful. Molten material may release toxic, and irritating fumes.

Inhalation: During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

Skin Contact: Dust may cause irritation in skin folds or by contact in combination with tight clothing. Contact with hot, molten metal will cause thermal burns. Removal of solidified molten material from skin requires medical assistance.

Eye Contact: Dust generated from material cutting may cause a slight irritation. Slivers may be generated, which could cause mechanical irritation or injure the eye. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Ingestion: If large amounts are ingested: Gastrointestinal irritation.

08/28/2018 EN (English US) 3/21

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Chronic Symptoms: May cause cancer. May damage fertility or the unborn child. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Silicon: Can cause chronic bronchitis and narrowing of the airways. Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Vanadium: May cause gastrointestinal discomfort, renal damage, nervous system depression and irritation of the respiratory passages. May also cause cardiac palpitations and asthma. Lead: Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Chronic dermal exposure to sulfur dust has been linked to headache, vertigo, irritation to the airways, breathing difficulties, coordination disturbances, accelerated pulse, hypotonia, cramps and unconsciousness. Frequent dermal contact with sulfur dusts mainly caused skin damage in the form of eczematous or ulcerous changes.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use halogenated extinguishing agents on small chips or fines. Do not use water when molten material is involved, contact of hot product with water will result in a violent expansion as the water turns to steam causing explosion with massive force.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but will burn at high temperatures. Small chips, turnings, dust and fines from processing may be readily ignitable.

Explosion Hazard: Product is not explosive. Dust generated from processing may present a dust explosion hazard.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Do not breathe fumes from fires or vapors from decomposition. Keep upwind. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Firefighters must use full bunker gear including NIOSH-approved positive-pressure self-contained breathing apparatus to protect against potential hazardous combustion and decomposition products.

Hazardous Combustion Products: Metallic oxides. Nickel oxides. Iron oxides. If heated to the point of fume generation zinc fumes may cause metal fume fever. Otherwise, zinc is non-toxic. Hydrocarbons.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe dust or fumes.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

08/28/2018 EN (English US) 4/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Do not allow to enter drains or water courses.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Collect scrap for recycling. If molten: contain the flow using dry sand or salt flux as a dam. Do not use shovels or hand tools to halt the flow of molten material. Allow the spill to cool before re-melting as scrap.

Methods for Cleaning Up: Avoid generation of dust during clean-up of spills. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up. Use only non-sparking tools. Use explosion-proof equipment.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Risk of thermal burns on contact with molten product. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations. May be a potential hazard under the following conditions:

- Small chunks, dust or fines in contact with water can generate flammable or toxic gases. These gases could present an explosion hazard in confined or poorly ventilated spaces.
- Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide). Moisture entrapped by molten metal can be explosive. Contact of molten aluminum with certain metal oxides can initiate a thermite reaction. Finely divided metals (e.g., powders or wire) may have enough surface oxide to produce thermite reactions/explosions.

Precautions for Safe Handling: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid creating or spreading dust. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Ensure there is adequate ventilation. Wear recommended personal protective equipment.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke in areas where product is used.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in original container. Store in a dry, cool place. Store in a well-ventilated place. Keep container tightly closed.

Incompatible Materials: Oxidizers. Acids. Bases. Mineral acids. Corrosive substances in contact with metals may produce flammable hydrogen gas.

7.3. Specific End Use(s)

Solid Product, Various Forms and Uses.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Nickel (7440-02-0)		
USA ACGIH	ACGIH TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Suspected as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.015 mg/m ³
USA IDLH	US IDLH (mg/m³)	10 mg/m³
Alberta	OEL TWA (mg/m³)	1.5 mg/m³
British Columbia	OEL TWA (mg/m³)	0.05 mg/m ³
Manitoba	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	1 mg/m³

08/28/2018 EN (English US) 5/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		According To The Hazardous Products Regulation (February 11, 2015).
Newfoundland & Labrador	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Nunavut	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Ontario	OEL TWA (mg/m³)	1 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	1 mg/m³
Chromium (7440-47-3)	, 3, ,	1 0.
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.5 mg/m ³
USA IDLH	US IDLH (mg/m³)	250 mg/m³
Alberta	OEL TWA (mg/m³)	0.5 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.5 mg/m ³
Manitoba	OEL TWA (mg/m³)	0.5 mg/m³
New Brunswick	OEL TWA (mg/m³)	0.5 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.5 mg/m³
Nova Scotia	OEL TWA (mg/m³)	0.5 mg/m³
Nunavut	OEL STEL (mg/m³)	1.5 mg/m³ (metal)
Nunavut	OEL TWA (mg/m³)	0.5 mg/m³ (metal)
Northwest Territories	OEL STEL (mg/m³)	1.5 mg/m³ (metal)
Northwest Territories	OEL TWA (mg/m³)	0.5 mg/m³ (metal)
Ontario	OEL TWA (mg/m³)	0.5 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	0.5 mg/m³
Québec	VEMP (mg/m³)	0.5 mg/m³
Saskatchewan	OEL STEL (mg/m³)	1.5 mg/m³
Saskatchewan	OEL TWA (mg/m³)	0.5 mg/m ³
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	0.1 mg/m³
Manganese (7439-96-5)	, ,	1 5
USA ACGIH	ACGIH TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
	/ (g/ /	0.1 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	5 mg/m³ (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³ (fume)
USA NIOSH	NIOSH REL (STEL) (mg/m³)	3 mg/m³
USA IDLH	US IDLH (mg/m³)	500 mg/m ³
Alberta	OEL TWA (mg/m³)	0.2 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.2 mg/m ³
Manitoba	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
	, G, ,	0.1 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	0.2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
		0.1 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)

08/28/2018 EN (English US) 6/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

The state of the s	Total Total Control Co	Ations And According to the Hazardous Products Regulation (Pebruary 11, 2015).	
Niconacona	OFI CTEL /m = /3\	0.1 mg/m³ (inhalable particulate matter)	
Nunavut	OEL STEL (mg/m³)	0.6 mg/m ³	
Nunavut	OEL TWA (mg/m³)	0.2 mg/m³	
Northwest Territories	OEL STEL (mg/m³)	0.6 mg/m ³	
Northwest Territories	OEL TWA (mg/m³)	0.2 mg/m ³	
Ontario	OEL TWA (mg/m³)	0.2 mg/m ³	
Prince Edward Island	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)	
		0.1 mg/m³ (inhalable particulate matter)	
Québec	VEMP (mg/m³)	0.2 mg/m³ (total dust and fume)	
Saskatchewan	OEL STEL (mg/m³)	0.6 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	0.2 mg/m ³	
Yukon	OEL Ceiling (mg/m³)	5 mg/m ³	
Molybdenum (7439-98-7)			
	Internal TWA (mg/m³)	5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)	
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)	
	, 3, ,	3 mg/m³ (respirable particulate matter)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)	
	, , , , , ,	15 mg/m³ (Molybdenum (as Mo), Insoluble Compounds	
		(Total dust)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)	
USA IDLH	US IDLH (mg/m³)	5000 mg/m ³	
Alberta	OEL TWA (mg/m³)	10 mg/m³ (total)	
		3 mg/m³ (respirable)	
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (respirable)	
		10 mg/m³ (inhalable)	
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
		10 mg/m³ (inhalable particulate matter)	
Newfoundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
		10 mg/m³ (inhalable particulate matter)	
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
	(3, ,	10 mg/m³ (inhalable particulate matter)	
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (metal-inhalable fraction)	
	, ,	6 mg/m³ (metal-respirable fraction)	
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (metal-inhalable fraction)	
		3 mg/m³ (metal-respirable fraction)	
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (metal-inhalable fraction)	
	· · · · · · · · · · · · · · · ·	6 mg/m³ (metal-respirable fraction)	
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (metal-inhalable fraction)	
		3 mg/m³ (metal-respirable fraction)	
Ontario	OEL TWA (mg/m³)	10 mg/m³ (metal-inhalable)	
		3 mg/m³ (metal-respirable)	
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
	0== (8/ /	10 mg/m³ (inhalable particulate matter)	
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)	
	· · · · · · · · · · · · · · · ·	6 mg/m³ (respirable fraction)	
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)	
	(3 mg/m³ (respirable fraction)	
Silicon (7440-21-3)	<u> </u>	5 (
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)	
OJA OJITA	OSHA FLE (TWA) (IIIB/III)	5 mg/m³ (respirable fraction)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)	
USA NIUSTI	NOSH KEE (TWA) (HIS/III-)	5 mg/m³ (respirable dust)	
	1	5 mg/m (respirable dust)	

08/28/2018 EN (English US) 7/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		ons And According To The Hazardous Products Regulation (February 11, 2015).	
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)	
		3 mg/m³ (respirable fraction)	
New Brunswick	OEL TWA (mg/m³)	10 mg/m³	
Nunavut	OEL STEL (mg/m³)	20 mg/m ³	
Nunavut	OEL TWA (mg/m³)	10 mg/m ³	
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³	
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³	
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline	
		silica-total dust)	
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³	
Yukon	OEL STEL (mg/m³)	20 mg/m ³	
Yukon	OEL TWA (mg/m³)	30 mppcf	
		10 mg/m ³	
Copper (7440-50-8)			
USA ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³ (fume)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³ (dust and mist)	
		0.1 mg/m³ (fume)	
USA IDLH	US IDLH (mg/m³)	100 mg/m³ (dust, fume and mist)	
Alberta	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
British Columbia	OEL TWA (mg/m³)	1 mg/m³ (dust and mist)	
		0.2 mg/m³ (fume)	
Manitoba	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
New Brunswick	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Newfoundland & Labrador	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
Nova Scotia	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
Nunavut	OEL STEL (mg/m³)	3 mg/m³ (dust and mist)	
		0.6 mg/m³ (fume)	
Nunavut	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Northwest Territories	OEL STEL (mg/m³)	3 mg/m³ (dust and mist)	
		0.6 mg/m³ (fume)	
Northwest Territories	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Ontario	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Prince Edward Island	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
Québec	VEMP (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Saskatchewan	OEL STEL (mg/m³)	0.6 mg/m³ (fume)	
		3 mg/m³ (dust and mist)	
Saskatchewan	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Yukon	OEL STEL (mg/m³)	0.2 mg/m³ (fume)	
		2 mg/m³ (dust and mist)	
Yukon	OEL TWA (mg/m³)	0.2 mg/m³ (fume)	
		1 mg/m³ (dust and mist)	
Cobalt (7440-48-4)			

08/28/2018 EN (English US) 8/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA ACGIH	ACGIH TWA (mg/m³)	0.02 mg/m ³	
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to	
OSA ACGIII	Acontenental category	Humans	
USA ACGIH	Biological Exposure Indices (BEI)	15 μg/l Parameter: Cobalt - Medium: urine - Sampling	
	Biological Exposure malees (BEI)	time: end of shift at end of workweek (nonspecific)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (dust and fume)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (dust and fume)	
USA IDLH	US IDLH (mg/m³)	20 mg/m³ (dust and fume)	
Alberta	OEL TWA (mg/m³)	0.02 mg/m³	
British Columbia	OEL TWA (mg/m³)	0.02 mg/m ³	
Manitoba	OEL TWA (mg/m³)	0.02 mg/m³	
New Brunswick	OEL TWA (mg/m³)	0.02 mg/m³	
Newfoundland & Labrador	OEL TWA (mg/m³)	0.02 mg/m³	
Nova Scotia	OEL TWA (mg/m³)	0.02 mg/m³	
Nunavut	OEL STEL (mg/m³)	0.06 mg/m ³	
Nunavut	OEL TWA (mg/m³)	0.02 mg/m ³	
Northwest Territories	OEL STEL (mg/m³)	0.06 mg/m ³	
Northwest Territories	OEL TWA (mg/m³)	0.02 mg/m ³	
Ontario	OEL TWA (mg/m³)	0.02 mg/m ³	
Prince Edward Island	OEL TWA (mg/m³)	0.02 mg/m ³	
Québec	VEMP (mg/m³)	0.02 mg/m ³	
Saskatchewan	OEL STEL (mg/m³)	0.06 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	0.02 mg/m³	
Yukon	OEL STEL (mg/m³)	0.15 mg/m³ (dust and fume)	
Yukon	OEL TWA (mg/m³)	0.05 mg/m³ (dust and fume)	
Tungsten (7440-33-7)			
USA ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m ³	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m ³	
Alberta	OEL STEL (mg/m³)	10 mg/m ³	
Alberta	OEL TWA (mg/m³)	5 mg/m ³	
British Columbia	OEL STEL (mg/m³)	10 mg/m ³	
British Columbia	OEL TWA (mg/m³)	5 mg/m ³	
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
Newfoundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
Nunavut	OEL STEL (mg/m³)	10 mg/m ³	
Nunavut	OEL TWA (mg/m³)	5 mg/m ³	
Northwest Territories	OEL STEL (mg/m³)	10 mg/m ³	
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³	
Ontario	OEL STEL (mg/m³)	10 mg/m ³	
Ontario	OEL TWA (mg/m³)	5 mg/m³	
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)	
Saskatchewan	OEL STEL (mg/m³)	10 mg/m³	
Saskatchewan	OEL TWA (mg/m³)	5 mg/m³	
Yukon	OEL STEL (mg/m³)	10 mg/m³	
Yukon	OEL TWA (mg/m³)	5 mg/m ³	
Aluminum (7429-90-5)	,		
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)	
00/20/2040	FAL(F!:-b-LIC)	5 mg/m³ (respirable fraction)	

08/28/2018 EN (English US) 9/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		According To The Hazardous Products Regulation (February 11, 2015).	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)	
		5 mg/m³ (respirable dust)	
Alberta	OEL TWA (mg/m³)	10 mg/m³ (dust)	
British Columbia	OEL TWA (mg/m³)	1 mg/m³ (respirable)	
Manitoba	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (metal dust)	
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (metal-dust)	
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (metal-dust)	
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (metal-dust)	
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (metal-dust)	
Ontario	OEL TWA (mg/m³)	1 mg/m³ (respirable)	
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
Québec	VEMP (mg/m³)	10 mg/m³	
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (dust)	
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (dust)	
Vanadium (7440-62-2)			
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	0.5 mg/m³ (respirable dust)	
		0.1 mg/m³ (fume)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	3 mg/m³	
Tantalum (7440-25-7)			
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³ (dust)	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³ (dust)	
USA IDLH	US IDLH (mg/m³)	2500 mg/m³ (dust)	
Alberta	OEL TWA (mg/m³)	5 mg/m³ (dust)	
British Columbia	OEL TWA (mg/m³)	5 mg/m³	
New Brunswick	OEL TWA (mg/m³)	5 mg/m³ (dust)	
Nunavut	OEL STEL (mg/m³)	10 mg/m³ (metal)	
Nunavut	OEL TWA (mg/m³)	5 mg/m³ (metal)	
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³ (metal)	
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³ (metal)	
Québec	VEMP (mg/m³)	5 mg/m³ (dust)	
Saskatchewan	OEL STEL (mg/m³)	10 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	5 mg/m ³	
Yukon	OEL STEL (mg/m³)	10 mg/m ³	
Yukon	OEL TWA (mg/m³)	5 mg/m³	
Lead (7439-92-1)			
USA ACGIH	ACGIH TWA (mg/m³)	0.05 mg/m ³	
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to	
LICA ACCILI	Dialogical Evacous to diseas (DEI)	Humans	
USA ACGIH	Biological Exposure Indices (BEI)	200 μg/l Parameter: Lead - Medium: blood - Sampling	
		time: not critical (Note: Persons applying this BEI are	
		encouraged to counsel female workers of child-bearing age	
		about the risk of delivering a child with a PbB (lead in blood level) over the current CDC reference value.)	
LICA OCHA	OSHA DEL (T\\/\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	50 μg/m ³	
USA OSHA USA NIOSH	OSHA PEL (TWA) (mg/m³) NIOSH REL (TWA) (mg/m³)	0.05 mg/m ³	
USA IDLH	US IDLH (mg/m³)	100 mg/m ³	
	OEL TWA (mg/m³)	0.05 mg/m ³	
Alberta	OEL TWA (IIIg/III ⁻)	U.UJ IIIK/III	

08/28/2018 EN (English US) 10/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

According to reactal Register / Vol. 77, No	. 30 / Monday, March 20, 2012 / Rules And Regulations And A	According to the Hazardous Products Regulation (February 11, 2015).	
British Columbia	OEL TWA (mg/m³)	0.05 mg/m ³	
Manitoba	OEL TWA (mg/m³)	0.05 mg/m ³	
New Brunswick	OEL TWA (mg/m³)	0.05 mg/m ³	
Newfoundland & Labrador	OEL TWA (mg/m³)	0.05 mg/m ³	
Nova Scotia	OEL TWA (mg/m³)	0.05 mg/m ³	
Nunavut	OEL STEL (mg/m³)	0.15 mg/m ³	
Nunavut	OEL TWA (mg/m³)	0.05 mg/m ³	
Northwest Territories	OEL STEL (mg/m³)	0.15 mg/m ³	
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m ³	
Ontario	OEL TWA (mg/m³)	0.05 mg/m³ (designated substances regulation)	
		0.05 mg/m³ (applies to workplaces to which the designated	
		substances regulation does not apply)	
Prince Edward Island	OEL TWA (mg/m³)	0.05 mg/m ³	
Québec	VEMP (mg/m³)	0.05 mg/m ³	
Saskatchewan	OEL STEL (mg/m³)	0.15 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m ³	
Yukon	OEL STEL (mg/m³)	0.45 mg/m³ (dust and fume)	
Yukon	OEL TWA (mg/m³)	0.15 mg/m³ (dust and fume)	
Paraffin oils (8012-95-1)			
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ (excluding metal working fluids, highly & severely	
	(,)	refined-inhalable particulate matter)	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen highly and severely	
	,	refined, Suspected Human Carcinogen highly and severely	
		refined	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³	
USA IDLH	US IDLH (mg/m³)	2500 mg/m ³	
Alberta	OEL STEL (mg/m³)	10 mg/m³	
Alberta	OEL TWA (mg/m³)	5 mg/m³	
British Columbia	OEL TWA (mg/m³)	0.2 mg/m³ (mildly refined)	
	, ,	1 mg/m³ (severely refined)	
Manitoba	OEL TWA (mg/m³)	5 mg/m³ (excluding metal working fluids, highly & severely	
	, ,	refined-inhalable particulate matter)	
New Brunswick	OEL STEL (mg/m³)	10 mg/m ³	
New Brunswick	OEL TWA (mg/m³)	5 mg/m³ (as sampled by a method that does not collect	
		vapor)	
Newfoundland & Labrador	OEL TWA (mg/m³)	5 mg/m³ (excluding metal working fluids, highly & severely	
		refined-inhalable particulate matter)	
Nova Scotia	OEL TWA (mg/m³)	5 mg/m³ (excluding metal working fluids, highly & severely	
		refined-inhalable particulate matter)	
Nunavut	OEL STEL (mg/m³)	10 mg/m ³	
Nunavut	OEL TWA (mg/m³)	5 mg/m³	
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³	
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³	
Ontario	OEL TWA (mg/m³)	5 mg/m³ (pure, highly and severely refined, excluding	
		metal working fluids-inhalable)	
Prince Edward Island	OEL TWA (mg/m³)	5 mg/m³ (excluding metal working fluids, highly & severely	
	-	refined-inhalable particulate matter)	
Québec	VECD (mg/m³)	10 mg/m³ (mist)	
Québec	VEMP (mg/m³)	5 mg/m³ (mist)	
Saskatchewan	OEL STEL (mg/m³)	10 mg/m ³	
t—————————————————————————————————————			

08/28/2018 EN (English US) 11/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL TWA (mg/m³)	5 mg/m³	
Yukon	OEL STEL (mg/m³)	10 mg/m ³	
Yukon	OEL TWA (mg/m³)	5 mg/m ³	
Nitrogen (7727-37-9)			
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen	
		Content	
Sulfur (7704-34-9)			
Alberta	OEL TWA (mg/m³)	10 mg/m³	

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountain capability should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. In powdered form: Avoid dust production. Take precautionary measures against static discharges. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Impermeable protective gloves.

Eye and Face Protection: Chemical safety goggles. Welders should wear goggles or safety glasses with side shields that comply with ANSI Z87.1 under welding helmets and always wear goggles or other suitable eye protection when gas welding or oxygen cutting. **Skin and Body Protection:** Wear suitable protective clothing.

Respiratory Protection: Fumes and dust: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Thermal Hazard Protection: When working with hot material, use suitable thermally protective clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties		
Physical State	:	Solid
Appearance	:	Gray; Metallic
Odor	:	Odorless
Odor Threshold	:	Not available
рН	:	Not available
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	Not available
Flash Point	:	Not available
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20°C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	Not available
Solubility	:	Water: Insoluble
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available

08/28/2018 EN (English US) 12/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity: Hazardous reactions will not occur under normal conditions.
- **10.2.** Chemical Stability: Stable under recommended handling and storage conditions (see Section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Dust, chips, or ribbons can be ignited more easily, by an ignition source, by improper machining, or by spontaneous combustion if finely divided and damp.
- **10.5. Incompatible Materials:** Oxidizers. Acids. Bases. Mineral acids. Corrosive substances in contact with metals may produce flammable hydrogen gas.
- 10.6. Hazardous Decomposition Products: None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Oral: Not classified Acute Toxicity (Dermal): Not classified Acute Toxicity (Inhalation): Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified **Carcinogenicity:** May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.
Reproductive Toxicity: May damage fertility or the unborn child.
Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

Symptoms/Injuries After Skin Contact: Dust may cause irritation in skin folds or by contact in combination with tight clothing. Contact with hot, molten metal will cause thermal burns. Removal of solidified molten material from skin requires medical assistance. Symptoms/Injuries After Eye Contact: Dust generated from material cutting may cause a slight irritation. Slivers may be generated, which could cause mechanical irritation or injure the eye. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Symptoms/Injuries After Ingestion: If large amounts are ingested: Gastrointestinal irritation.

Chronic Symptoms: May cause cancer. May damage fertility or the unborn child. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Silicon: Can cause chronic bronchitis and narrowing of the airways. Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Vanadium: May cause gastrointestinal discomfort, renal damage, nervous system depression and irritation of the respiratory passages. May also cause cardiac palpitations and asthma. Lead: Exposure can result in lassitude (weakness, exhaustion),

08/28/2018 EN (English US) 13/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Chronic dermal exposure to sulfur dust has been linked to headache, vertigo, irritation to the airways, breathing difficulties, coordination disturbances, accelerated pulse, hypotonia, cramps and unconsciousness. Frequent dermal contact with sulfur dusts mainly caused skin damage in the form of eczematous or ulcerous changes.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

LD50 and LC50 Data:			
Iron (7439-89-6)			
LD50 Oral Rat	98.6 g/kg		
Nickel (7440-02-0)			
LD50 Oral Rat	> 9000 mg/kg		
Chromium (7440-47-3)			
LD50 Oral Rat	> 5000 mg/kg		
LC50 Inhalation Rat	> 5.41 mg/l/4h		
Manganese (7439-96-5)			
LD50 Oral Rat	> 2000 mg/kg		
LC50 Inhalation Rat	> 5.14 mg/l/4h		
Molybdenum (7439-98-7)			
LD50 Oral Rat	> 2000 mg/kg		
LD50 Dermal Rat	> 2000 mg/kg		
LC50 Inhalation Rat	> 3.92 mg/l/4h		
Silicon (7440-21-3)			
LD50 Oral Rat	3160 mg/kg		
Cobalt (7440-48-4)			
LD50 Oral Rat	215.9 - 1140 mg/kg		
LC50 Inhalation Rat	> 10 mg/l (Exposure time: 1 h)		
LC50 Inhalation Rat	< 0.05 mg/l/4h		
ATE US/CA (dust, mist)	0.01 mg/l/4h		
Carbon (7440-44-0)			
LD50 Oral Rat	> 10000 mg/kg		
Tantalum (7440-25-7)			
LD50 Oral Rat	> 2000 mg/kg		
LD50 Dermal Rat	> 2000 mg/kg		
Niobium (7440-03-1)			
LD50 Oral Rat	> 10 g/kg		
Paraffin oils (8012-95-1)			
LD50 Oral Rat	> 24 g/kg		
LC50 Inhalation Rat	2062 ppm/4h		
ATE US/CA (dust, mist)	1.50 mg/l/4h		
Sulfur (7704-34-9)			
LD50 Oral Rat	> 3000 mg/kg		
LD50 Dermal Rabbit	> 2000 mg/kg		
LC50 Inhalation Rat	> 9.23 mg/l/4h		
Nickel (7440-02-0)			
IARC Group	2B		
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.		
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.		
Chromium (7440-47-3)	<u> </u>		
IARC Group	3		
Cobalt (7440-48-4)			
IARC Group	2B		
0.00p			

08/28/2018 EN (English US) 14/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
Lead (7439-92-1)		
IARC Group	2A	
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
Paraffin oils (8012-95-1)		
IARC Group	1	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: This product contains components that are environmentally hazardous and small chips and dust from processing may be toxic to aquatic life.

Nickel (7440-02-0)		
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)	
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	15.3 mg/l	
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
Manganese (7439-96-5)		
NOEC Chronic Fish	3.6 mg/l (Exposure time: 96h; Species: Oncorhynchus mykiss)	
Cobalt (7440-48-4)		
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	
Sulfur (7704-34-9)		
LC50 Fish 1	866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	
EC50 Daphnia 1	736 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	

12.2. Persistence and Degradability

Stainless Steels	
Persistence and Degradability Not readily biodegradable.	
Copper (7440-50-8)	
Persistence and Degradability	Not readily biodegradable.

12.3. Bioaccumulative Potential

Cobalt (7440-48-4)	
BCF Fish 1	(no bioaccumulation)

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information: Avoid unnecessary release into the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Recycle where possible and/or dispose of spent material such as metals and metal-bearing waste and submerged arc welding (SAW) flux/slag appropriately.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

08/28/2018 EN (English US) 15/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

14.3. In Accordance with IATA Not regulated for transport 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations 15.1.

15.1. US Federal Regulations		
Stainless Steels		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
	Immediate (acute) health hazard	
Iron (7439-89-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Nickel (7440-02-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section	on 313	
CERCLA RQ	100 lb (only applicable if particles are < 100 μm)	
SARA Section 313 - Emission Reporting	0.1 %	
Chromium (7440-47-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section	on 313	
CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is	
	required if the diameter of the pieces of the solid metal released is	
	>100 μm	
SARA Section 313 - Emission Reporting	1%	
Manganese (7439-96-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section	on 313	
SARA Section 313 - Emission Reporting	1%	
Molybdenum (7439-98-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Silicon (7440-21-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Copper (7440-50-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section		
CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is	
	required if the diameter of the pieces of the solid metal released is	
	>100 μm	
SARA Section 313 - Emission Reporting	1%	
Cobalt (7440-48-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section	on 313	
SARA Section 313 - Emission Reporting	0.1 %	
Tungsten (7440-33-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Aluminum (7429-90-5)	·	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313		
SARA Section 313 - Emission Reporting 1 % (dust or fume only)		
Titanium (7440-32-6)	•	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Carbon (7440-44-0)	, 1	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the officed states 136A (Toxic substances control Act	, inventory	

08/28/2018 EN (English US) 16/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Vanadium (7440-62-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Subject to reporting requirements of United States SARA Section	•	
ARA Section 313 - Emission Reporting 1 % (except when contained in an alloy)		
Tantalum (7440-25-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Niobium (7440-03-1)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Lead (7439-92-1)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Subject to reporting requirements of United States SARA Section	on 313	
CERCLA RQ	10 lb no reporting of releases of this hazardous substance is	
	required if the diameter of the pieces of the solid metal released is	
	>100 μm	
SARA Section 313 - Emission Reporting	0.1 %	
Paraffin oils (8012-95-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Nitrogen (7727-37-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Sulfur (7704-34-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

15.2. US State Regulations

Stainless Steels	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.

California Proposition 65



This product can expose you to Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

	0	0 0		
Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Nickel (7440-02-0)	Х			
Cobalt (7440-48-4)	Х			
Lead (7439-92-1)	Х	X	X	Х

Nickel (7440-02-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Chromium (7440-47-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Manganese (7439-96-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Molybdenum (7439-98-7)

08/28/2018 EN (English US) 17/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Silicon (7440-21-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Copper (7440-50-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Cobalt (7440-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Tungsten (7440-33-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Aluminum (7429-90-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Titanium (7440-32-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

Vanadium (7440-62-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Tantalum (7440-25-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Lead (7439-92-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Paraffin oils (8012-95-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Nitrogen (7727-37-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Sulfur (7704-34-9)

08/28/2018 EN (English US) 18/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Iron (7439-89-6)

Listed on the Canadian DSL (Domestic Substances List)

Nickel (7440-02-0)

Listed on the Canadian DSL (Domestic Substances List)

Chromium (7440-47-3)

Listed on the Canadian DSL (Domestic Substances List)

Manganese (7439-96-5)

Listed on the Canadian DSL (Domestic Substances List)

Molybdenum (7439-98-7)

Listed on the Canadian DSL (Domestic Substances List)

Silicon (7440-21-3)

Listed on the Canadian DSL (Domestic Substances List)

Copper (7440-50-8)

Listed on the Canadian DSL (Domestic Substances List)

Cobalt (7440-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Tungsten (7440-33-7)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List)

Titanium (7440-32-6)

Listed on the Canadian DSL (Domestic Substances List)

Carbon (7440-44-0)

Listed on the Canadian DSL (Domestic Substances List)

Vanadium (7440-62-2)

Listed on the Canadian DSL (Domestic Substances List)

Tantalum (7440-25-7)

Listed on the Canadian DSL (Domestic Substances List)

Niobium (7440-03-1)

Listed on the Canadian DSL (Domestic Substances List)

Lead (7439-92-1)

Listed on the Canadian DSL (Domestic Substances List)

Paraffin oils (8012-95-1)

Listed on the Canadian DSL (Domestic Substances List)

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

Sulfur (7704-34-9)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest

: 08/28/2018

Revision
Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

08/28/2018 EN (English US) 19/21

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

GHS Full Text Phrases:

uli Text Fillases.		
Acute Tox. 1	Acute toxicity (inhalation:dust,mist) Category 1	
(Inhalation:dust,mist)	A suite terricity (in helption which moint) Cotago m. A	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1	
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 1 Hazardous to the aquatic environment - Acute Hazard Category 3	
Aquatic Acute 3 Aquatic Chronic 1	Hazardous to the aquatic environment - Acute Hazard Category 3 Hazardous to the aquatic environment - Chronic Hazard Category 1	
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 1	
Asp. Tox. 1	Aspiration hazard Category 1	
Carc. 1B	Carcinogenicity Category 1B	
Carc. 2	Carcinogenicity Category 1B Carcinogenicity Category 2	
Comb. Dust	Combustible Dust	
Eye Irrit. 2A		
· ·	Serious eye damage/eye irritation Category 2A	
Lact	Reproductive toxicity (Lact.)	
Press. Gas (Comp.)	Gases under pressure Compressed gas	
Repr. 1A	Reproductive toxicity Category 1A	
Repr. 1B	Reproductive toxicity Category 1B	
Repr. 2	Reproductive toxicity Category 2	
Resp. Sens. 1B	Respiratory sensitization, Category 1B	
Simple Asphy	Simple Asphyxiant	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization, Category 1	
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1	
H280	Contains gas under pressure; may explode if heated	
H302	Harmful if swallowed	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H330	Fatal if inhaled	
H332	Harmful if inhaled	
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled	
H350	May cause cancer	
H351	Suspected of causing cancer	
H360	May damage fertility or the unborn child	
H361	Suspected of damaging fertility or the unborn child	
H362	May cause harm to breast-fed children	
H372	Causes damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
H402	Harmful to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H413	May cause long lasting harmful effects to aquatic life	
	May displace oxygen and cause rapid suffocation	
t		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

08/28/2018 EN (English US) 20/21

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

NA GHS SDS 2015 (Can, US)

08/28/2018 EN (English US) 21/21